

Refurbished CISCO A9KV-V2-DC-A Datasheet

CISCO > ROUTERS

Cisco ASR 9000 Series Aggregation Services Routers

Cisco ASR 9000v and Cisco ASR 9000v-V2 Interfaces

44 Small Form-Factor Pluggable (SFP) ports (10, 100 and 1000 Mbps)	SFP ports deliver 10, 100, and 1000 Mbps services. See the Cisco Optical Pluggable Modules for ASR 9000v Data Sheet for details on the supported pluggable ports.
4 SFP+ 10-GE Pluggable Ports	SFP+ interfaces provide mix-and-match interface types. For a complete list of supported interfaces, see the Cisco Optical Pluggable Modules for ASR 9000v Data Sheet for details on the supported pluggable ports.
AC	Cisco ASR 9000v AC Chassis only, this three-connector receptacle is intended for use with external AC cables.
ANSI DC-A and DC-B	Cisco ASR 9000v DC-A Chassis only, these two redundant DC power inputs are ANSI compliant.
ETSI DC-A and DC-B	Cisco ASR 9000v DC-E Chassis only, these two redundant DC power inputs are ETSI compliant.
EOBC	Ethernet management port that can be optionally used for local Cisco ASR 9000v management.
Console	Serial port that can be optionally used for local Cisco ASR 9000v management.
Time of day (ToD) and packets per second (PPS)	Reserved for future use.

The next steps...

ORDER NOW

VIEW ONLINE

Tel: +44 (0)1279 408 777

Email: sales@gocomsys.com

Website: www.gocomsys.com