

# Refurbished CISCO ASA5520-AIP-NFR-K9 Datasheet

CISCO > SECURITY

## Cisco ASA 5500-X Series Firewalls

### Characteristics of Cisco ASA 5500 Series AIP SSM Models

Operating	
Temperature	32 to 104°F (0 to 40°C)
Nonoperating	
Temperature	-13 to 158°F (-25 to 70°C)
Physical Specifications	
Dimensions (H x W x D)	1.70 x 6.80 x 12.25 in. (4.32 x 17.27 x 31.12 cm)
Regulatory and Standards Compliance	
Safety	UL 60950, CSA C22.2 No. 60950, EN 60950 IEC 60950, AS/NZS60950
Electromagnetic Compatibility (EMC)	CE marking, FCC Part 15 Class A, AS/NZS CISPR22 Class A, VCCI Class A, EN55022 Class A, CISPR22 Class A, EN61000-3-2, EN61000-3-3

### Characteristics of Cisco ASA 5500 Series CSC SSMs

Operating	
Temperature	32 to 104°F (0 to 40°C)
Nonoperating	
Temperature	-13 to 158°F (-25 to 70°C)
Physical Specifications	
Dimensions (H x W x D)	1.70 x 6.80 x 12.25 in. (4.32 x 17.27 x 31.12 cm)
Regulatory and Standards Compliance	
Safety	UL 60950, CSA C22.2 No. 60950, EN 60950 IEC 60950, AS/NZS60950
Electromagnetic Compatibility (EMC)	CE marking, FCC Part 15 Class A, AS/NZS CISPR22 Class A, VCCI Class A, EN55022 Class A, CISPR22 Class A, EN61000-3-2, EN61000-3-3

### Characteristics of Cisco ASA 5500 Series 4-Port Gigabit Ethernet SSMs

Technical Specifications	
Integrated LAN Ports	Four 10/100/1000BASE-T
Operating	
Temperature	32 to 104°F (0 to 40°C)
Nonoperating	
Temperature	-13 to 158°F (-25 to 70°C)
Physical Specifications	

---

<b>Dimensions (H x W x D)</b>	1.70 x 6.80 x 12.25 in. (4.32 x 17.27 x 31.12 cm)
<b>Regulatory and Standards Compliance</b>	
<b>Safety</b>	UL 60950, CSA C22.2 No. 60950, EN 60950 IEC 60950, AS/NZS60950
<b>Electromagnetic Compatibility (EMC)</b>	CE marking, FCC Part 15 Class A, AS/NZS CISPR22 Class A, VCCI Class A, EN55022 Class A, CISPR22 Class A, EN61000-3-2, EN61000-3-3

---

## The next steps...

---

**ORDER NOW**

**VIEW ONLINE**

**Tel: +44 (0)1279 408 777**

**Email: [sales@gocomsys.com](mailto:sales@gocomsys.com)**

**Website: [www.gocomsys.com](http://www.gocomsys.com)**