Tel: +44 (0)1279 408 777
Email: sales@gocomsys.com
Website: www.gocomsys.com

Refurbished CISCO C6800IA-48FPDR Datasheet

CISCO > SWITCHES

Cisco Catalyst 6800 Series Switches

PoE and PoE+ Power Capacity for Cisco Catalyst 6800IA

	Switch Model
Maximum Number of PoE+ (IEEE 802.3at) Ports	24 ports up to 30W
Maximum Number of PoE (IEEE 802.3af) Ports	48 ports up to 15.4W
Available PoE Power (Single PS Source)	740W

Cisco Catalyst 6800ia Series Hardware

	Hardware Specifications
Flash memory	128 MB
DRAM	512 MB
CPU	APM86392 600MHz dual core
Console ports	USB (Type-B), Ethernet (RJ-45)
Network management interface	10/100 Mbps Ethernet (RJ-45)
Egress Buffers	4 MB

Cisco Catalyst 6800ia Series Mechanical Specifications

	Models
FPS	1.75 x 16.0 x 17.5
MKS	4.45 x 40.8 x 44.5

Predicted Reliability

	Models
MTBF in Hours	233,370

Voltage and Power Ratings

	Model
Voltage (Autoranging)	100 to 240 VAC
Current	10A to 5A
Frequency	50 to 60 Hz

Safety and Compliance

Specification	
Regulatory compliance	Products should comply with CE Marking per directives 2004/108/EC and 2006/95/EC
Safety	UL 60950-1 Second Edition CAN/CSA-C22.2 No. 60950-1 Second Edition EN 60950-1 Second Edition IEC 60950-1 Second Edition AS/NZS 60950-1
EMC: Emissions	47CFR Part 15 (CFR 47) Class A AS/NZS CISPR22 Class A CISPR22 Class A EN55022 Class A ICES003 Class A VCCI Class A EN61000-3-2 EN61000-3-3 KN22 Class A CNS13438 Class A
EMC: Immunity	EN55024 CISPR24 EN300386 KN24
Environmental	Reduction of Hazardous Substances (RoHS) including Directive 2011/65/EU
Telco	Common Language Equipment Identifier (CLEI) code

The next steps...

ORDER NOW

VIEW ONLINE

Tel: +44 (0)1279 408 777

Email: sales@gocomsys.com

Website: www.gocomsys.com