

Refurbished CISCO C9200-24P-A Datasheet

CISCO > SWITCHES

Cisco Catalyst 9200 Series Switches

Cisco Catalyst 9200 Series Switch configurations

Modular uplink models

Modular uplink models	24 ports full PoE+
Modular uplink models	Modular uplink options
Modular uplink models	PWR-C5-600WAC
Modular uplink models	FRU redundant

PoE+ Power with primary and secondary power supplies

Model

Default primary power supply	PWR-C5-600WAC
Available PoE power with single primary power supply only	370W
Optional secondary power supply	PWR-C5-600WAC / PWR-C6-600WAC
Available PoE power with additional secondary power supply	740W

Stacking accessories

Model

C9200-STACK-KIT	Stack kit for C9200 SKUs only: Two data stack adapters and one data stack cable
C9200L-STACK-KIT	Stack kit for C9200L SKUs only: Two data stack adapters and one data stack cable
STACK-T4-50CM	Data stack 50 cm cable (default cable with Stack Kit)
STACK-T4-1M	Data stack 1 m cable
STACK T4-3M	Data stack 3 m cable

Bandwidth specifications

Description

Switching capacity	128 Gbps
Switch capacity with Stacking	288 Gbps
Forwarding rate	95.23 Mpps
Forwarding rate with Stacking	214 Mpps

Model Dimensions, Weight, and Mean time between failures metrics

Model	
Inches	1.73 x 17.5 x 13.8
Centimeters	4.4 x 44.5 x 35.0
Inches	1.73 x 17.5 x 15.4
Centimeters	4.4 x 44.5 x 39.1

Connectors

Connectors and cabling	1000BASE-T ports: RJ-45 connectors, 4-pair Cat 5E UTP cabling 1000BASE-T SFP-based ports: RJ-45 connectors, 4-pair Cat 5E UTP cabling 100BASE-FX, 1000BASE-SX, -LX/LH, -ZX, -BX10, dense wavelength-division multiplexing (DWDM) and Coarse Wavelength-Division Multiplexing (CWDM) SFP transceivers: LC fiber connectors (single-mode or multimode fiber) 10GBASE-SR, LR, LRM (only C9200), ER, ZR, DWDM SFP+ transceivers: LC fiber connectors (single-mode or multimode fiber) SFP+ connector Cisco StackWise-160/80 stacking ports: copper-based Cisco StackWise cabling Ethernet management port: RJ-45 connectors, 4-pair Cat 5 UTP cabling Management console port: RJ-45-to-DB9 cable for PC connections, USB-C adaptor, USB adaptor
Power connectors	Internal power supply connector: The internal power supply is an auto-ranging unit. It supports input voltages between 100 and 240 VAC. Use the supplied AC power cord to connect the AC power connector to an AC power outlet.

Power consumption of Standalone Catalyst 9200 Series switches

Full port traffic	600W (C5/C6)
Weighted average Pw	C9200-NM-4X1G
No link	115VAC
PoE test (no traffic)	43.57

Safety and compliance information

Description	
Description	Specification
Safety certifications	IEC 60950-1 UL 60950-1 CAN/CSA C22.2 No. 60950-1 EN 60950-1 AS/NZS 60950.1 Class I Equipment
Electromagnetic emissions certifications	47 CFR Part 15 CISPR 22 Class A CISPR 32 Class A CNS 13438 EN 300 386 EN 55022 Class A EN 55032 Class A EN61000-3-2 EN61000-3-3 ICES-003 Class A KN 32 TCVN 7189 Class A V-3 Class A CISPR 24 EN 300 386 EN 55024 KN 35 TCVN 7317
Environmental	Reduction of Hazardous Substances (ROHS) 5

The next steps...

ORDER NOW

VIEW ONLINE

Tel: +44 (0)1279 408 777

Email: sales@gocomsys.com

Website: www.gocomsys.com