Tel: +44 (0)1279 408 777
Email: sales@gocomsys.com
Website: www.gocomsys.com

Refurbished CISCO C9400-SUP-1 Datasheet

CISCO > SWITCHES

Cisco Catalyst 9400 Series Switches

Cisco Catalyst 9400 Supervisor Engine-1 and Supervisor Engine-1XL Uplink Options

Supervisor configuration	
Supervisor configuration	Uplink ports options
Single supervisor	8x 10 Gigabit Ethernet ports are active (ports 1 to 8) (2x 40 Gigabit Ethernet ports are disabled [ports 9 to 10])
Dual supervisors	Active supervisor: 4x 10 Gigabit Ethernet ports are active (ports 1 to 4) (the other 4x 10 Gigabit Ethernet ports are disabled); standby supervisor: 4x 10 Gigabit Ethernet ports (ports 1 to 4) (the other 4x10 Gigabit Ethernet ports are disabled)

Cisco Catalyst 9400 Supervisor Engine-1XL-Y Uplink Options

Supervisor configuration	
Supervisor configuration	Uplink ports options
Single supervisor	8x 10 Gigabit Ethernet ports are active (ports 1 to 8) (2x 40 Gigabit Ethernet ports are disabled [ports 9 to 10])
Dual supervisors	Active supervisor: 4x 10 Gigabit Ethernet ports are active (ports 1 to 4) (the other 4x 10 Gigabit Ethernet ports are disabled); standby supervisor: 4x 10 Gigabit Ethernet ports (ports 1 to 4) (the other 4x10 Gigabit Ethernet ports are disabled)

Dimensions, Weight, Acoustic, and MTBF Details

Physical specifications	(H x W x D): 1.6 x 14.92 x 14.57 in. (4.06 x 37.90 x 37.00 cm) Weight: 10 lb (4.5 kg)
Operating temperature	Normal operating temperature and altitudes: 23° to 113°F (-5° to +45°C), up to 6000 feet (1800 m) 23° to 104°F (-5° to +40°C), up to 10,000 feet (3000 m) Minimum ambient temperature for cold startup is 0°C Short-term exceptional conditions: 23° to 131°F (-5° to +55°C), up to 6000 feet (1800 m) 23° to 122°F (-5° to +50°C), up to 10,000 feet (3000 m) Not more than following in one-year period: 96 consecutive hours, or 360 hours total, or 15 occurrences
Storage temperature	40° to 158°F (-40° to 70°C)
Relative humidity operating and nonoperating noncondensing	10 to 95 percent, noncondensing
Altitude	-60 to 3000m
MTBF	C9400-SUP-1: 253,010 hours C9400-SUP-1XL: 253,010 hours C9400-SUP-1XL-Y: 237,670 hours

Safety and Compliance Information for the Cisco Catalyst 9400 Series

Description	
Description	Specifications

Safety certifications	UL 60950-1 CAN/CSA-C222.2 No. 60950-1 EN 60950-1 IEC 60950-1 AS/NZS 60950.1 IEEE 802.3
Electromagnetic emissions certifications	47 CFR Part 15 CISPR22 Class A EN 300 386 V1.6.1 EN 55022 Class A EN 55032 Class A CISPR 32 Class A EN61000-3-2 EN61000-3-3 ICES-003 Class A TCVN 7189 Class A V-3 Class A CISPR24 EN 300 386 EN55024 TCVN 7317
Environmental	Reduction Of Hazardous Substances (ROHS) 5

The next steps...

ORDER NOW

VIEW ONLINE

Tel: +44 (0)1279 408 777

Email: sales@gocomsys.com

Website: www.gocomsys.com