

Refurbished CISCO CAB-1900W-UK Datasheet

CISCO > STORAGE-NETWORKING

Cisco MDS 9500 Series Multilayer Directors

Product Specifications	
Power Consumption	
Power Consumption	Cisco MDS 9506
Power Consumption	Typical (Watts)
Power Consumption	1463
Environmental	Temperature, ambient operating: 32 to 104°F (0 to 40°C) Temperature, ambient non-operating and storage: -40 to 167°F (-40 to 75°C) Relative humidity, ambient (non-condensing) operating: 10 to 90% Relative humidity, ambient (non-condensing) non-operating and storage: 10 to 95% Altitude, operating: -197 to 6500 feet (-60 to 2000m)
Physical dimensions	Dimensions (H x W x D) 12.25 x 17.37 x 21.75 in (31.1 x 44.1 x 55.25 cm) -7 RU Chassis depth including cable guide is 26.75 in. (67.9 cm). All units rack mountable in standard 19 inch EIA rack
Weight	Chassis (includes fan tray): 46 lb (20.9 kg) Chassis fully configured with two supervisor/fabric modules, four switching modules, and two 1900W power supplies: 124 lb (56 kg)
Approvals and compliance	Safety compliance CE Marking UL 60950 CAN/CSA-C22.2 No. 60950 EN 60950 IEC 60950 TS 001 AS/NZS 3260 IEC60825 EN60825 21 CFR 1040 EMC compliance FCC Part 15 (CFR 47) Class A ICES-003 Class A EN 55022 Class A CISPR 22 Class A AS/NZS 3548 Class A VCCI Class A EN 55024 EN 50082-1 EN 61000-6-1 EN 61000-3-2 EN 61000-3-3 FIPS certified FIPS 140-2 Level 2

The next steps...

ORDER NOW

VIEW ONLINE

Tel: +44 (0)1279 408 777

Email: sales@gocomsys.com

Website: www.gocomsys.com