

Refurbished CISCO CAB-L620P-C19-US Datasheet

CISCO > SWITCHES

Cisco Catalyst 9400 Series Switches

Regulatory standards compliance	
Specification	
Specification	Standard
Regulatory compliance	CE Marking
Safety	UL 60950-1 CAN/CSA-C222.2 No. 60950-1 EN 60950-1 IEC 60950-1 AS/NZS 60950.1 IEEE 802.3
EMC	47 CFR Part 15 CISPR22 Class A KN 32 Class A EN 300 386 V1.6.1 EN 55022 Class A EN 55032 Class A CISPR 32 Class A EN61000-3-2 EN61000-3-3 ICES-003 Class A TCVN 7189 Class A V-3 Class A CNS13438 Class A CISPR24 EN 300 386 EN55024 TCVN 7317 KN35
Industry EMC, safety, and environmental standards	NEBS: Operating temperature: -5 to 55C Relative Humidity: 10-93% Operating Altitude: up to 1829 m (6000 ft) at 55C ETSI 300-019 Requirements are covered under GR-63-CORE with some deviations. SR-3580 NEBS level 3 (GR-63-CORE, to current issue, GR-1089-CORE, to current issue) ETS 300 019-2-1, Class 1.2 Storage ETS 300 019-2-2, Class 2.3 Transportation ETS 300 019-2-3, Class 3.2 Stationary EN50121-4 EN 300 386
ROHS compliance	ROHS5

MTBF information	
Part Number	
Part Number	Rated MTBF (Hours)
C9404R	2,077,070
C9407R	1,571,010
C9410R	1,404,840

The next steps...

ORDER NOW

VIEW ONLINE

Tel: +44 (0)1279 408 777

Email: sales@gocomsys.com

Website: www.gocomsys.com