Tel: +44 (0)1279 408 777
Email: sales@gocomsys.com
Website: www.gocomsys.com

Refurbished CISCO CIVS-IPC-VFM15-50 Datasheet

CISCO > PHYSICAL-SECURITY

Product Specifications

General	
Imaging Device	1/3-inch (effective)
Imager Type	CMOS
Imager Readout	Progressive scan
Maximum Resolution	1920 x 1080
Signal-to-Noise Ratio	50 dB
Auto Iris Lens Type	DC drive
Electronic Shutter Range	1~1/100,000 sec
Wide Dynamic Range	60 dB
White Balance Range	2,000 to 10,000K
Sensitivity	f/1.2; 2850K; SNR >24 dB Color (1x/33 ms): 0.5 lux Color SENS (15x/500 ms): 0.12 lux Mono (1x/33 ms): 0.25 lux Mono SENS (15x/500 ms): 0.03 lux
Dome Attenuation	Clear: Zero light loss Smoked: f/1.0 light loss
Construction	Back box: Cast aluminum Trim ring: Polycarbonate plastic Bubble: Acrylic plastic
Finish	White
Available Languages	English
Supported Protocols	TCP/IP, UDP/IP (Unicast), UPnP, DNS, DHCP, RTP, RTSP, NTP, IPv4, SNMP, QoS, HTTP, SMTP, FTP
Users	Up to 20 simultaneous users, depending on resolution settings (2 guaranteed streams)
Security Access	Password-protected
Electrical	
Port	RJ-45 connector for 100BASE-TX Auto MDI/MDI-X
Cable Type	Cat-5 or better for 100BASE-TX
Power Input	24 VAC or PoE (IEEE 802.3af class 3)
Power Consumption	6W
Current Consumption	PoE: < 200 mA maximum 24 VAC: < 295 mA nominal; < 390 mA maximum
Local Storage	Micro SD
Alarm Input	10 VDC maximum, 5 mA maximum
Alarm Output	0 to 15 VDC maximum, 75 mA maximum
Service Port	External 3-connector, 2.5-mm provides NTSC/PAL video output
Mechanical	

Lens Mount	CS-mount, adjustable
Environmental	
Operational Temperature	32 to 122ºF (0 to 50ºC)
Physical	
Dimensions (DxWxH)	5.4 x 3.1 x 3.0 in. (13.7 x 7.9 x 7.6 cm)
Video	
Video Encoding	H.264 base profile and MJPEG
Video Streams	Up to 2 simultaneous streams; the second stream is variable based on the setup of the primary stream
Supported Frame Rates	30, 15, 10, 5, 1
Video Encoding	H.264 base profile and MJPEG
Video Streams	Up to 2 simultaneous streams; the second stream is variable based on the setup of the primary stream
Supported Resolutions	1080P (1920 x 1080), 720P (1280 x 720), 4CIF (640 x 352), CIF (480 x 272), and QCIF (320 x 176)

The next steps...

ORDER NOW

VIEW ONLINE

Tel: +44 (0)1279 408 777

Email: sales@gocomsys.com

Website: www.gocomsys.com