Tel: +44 (0)1279 408 777
Email: sales@gocomsys.com
Website: www.gocomsys.com

Refurbished CISCO CP-CKEM-C Datasheet

CISCO > COLLABORATION-ENDPOINTS

Cisco Unified IP Phone 9900 and 8900 Series Accessories

Features and Benefits

Illuminated Buttons	
Off (dark)	Line available
Green, steady	Line in use
Red, steady	Line in use by someone else

Illuminated Page Buttons	
Off (dark)	Page not in focus
Green, steady	Page in focus

Hardware and Power-Saving Features	
Graphical display	The 4.3-in. graphical (TFT) color display provides 16-bit color depth and 480 x 272 effective pixel resolution, with backlight. The display also supports localization requiring double-byte Unicode encoding for fonts.
Articulation	You can articulate the display to match the same angle as the Cisco Unified IP Phone it is connected to.
Directory-number and feature buttons	The module has 18 physical buttons (36 with page key).
Page buttons	The two Page buttons are used to access each page of 18 buttons and provide phone status.
Sleep or inactivity mode	When Cisco Unified IP Phone 9971, 9951, and 8961 models are in power-saving sleep or inactivity mode, the Cisco Unified IP Color Key Expansion Module is also in sleep or inactivity mode. Pressing any button on the key expansion module causes the displays to awaken. The system administrator configures the inactivity period.

Cisco IP Color Key Expansion Module Hardware Support Compatibility

Cisco Unified IP Phone Model	Number of Cisco Unified IP Color Key Expansion Modules Supported
9971	3
9951	2
8961	1

Product Specifications

Physical dimensions (H x W x D)	
Physical dimensions (H x W x D)	9.21 x 5.04 x 1.61 in. (234 x 128 x 41 mm)
Weight	Charcoal: 1.03 lb (465g) White: 1.1 lb (498g)
Power	48 VDC, 117 mA maximum
Operating temperature	32 to 104°F (0 to 40°C)
Relative humidity	10 to 95%

Storage temperature	12 to 140°F (-10 to 60°C)
Approvals and compliance	http://www.cisco.com/en/US/docs/voice_ip_comm/cuipph/all_models/regulatory_compliance/english/install/guide/iphrcsi3.html

System Requirements

Phone Firmware/Media Control Server	Release
Cisco Unified IP Phone firmware	9.0(1) and later
Call-control compatibility	Cisco Unified Communications Manager 7.1(3) and later; Cisco Unified Survivable Remote Site Telephony (SRST) 7.1 (Cisco IOS Software Release 12.4(24)T) and later

The next steps...

ORDER NOW

VIEW ONLINE

Tel: +44 (0)1279 408 777

Email: sales@gocomsys.com

Website: www.gocomsys.com