

Refurbished CISCO DAT-USB-RM-72 Datasheet

CISCO > UNIFIED-COMMUNICATIONS

Cisco 7800 Series Media Convergence Servers

Product Specifications	
Processor at Product Introduction	
Processor (CPU)	Intel Woodcrest Xeon DP
Processor internal clock speed	2.33 GHz
Level 2 cache	4096 KB
Maximum processors	2
Processors installed	1
Memory	
Memory maximum	48 GB
Memory bus clock	667 MHz
Memory technology	PC2-5300 667 MHz DDR2 SDRAM
Multibit error mitigation	Advanced Error Checking and Correcting (AECC)
Total RAM slots	12
RAID Controller	
Controller model	IBM mezzanine ServeRAID-8k controller
Interface	Connected to motherboard
Cache	256 MB
Battery-backed write caching	Yes
Hard Disk	
Hard disk installed	Two 72.3-GB SAS drives
Hard-disk rotate processor module (RPM)	10,000
Hard-disk average seek time	4 ms
Hot-swappable bays	8
Hard-disk interface type	SAS
Network Interface Specifications	
Ethernet network interface card (NIC)	Dual onboard 10/100/1000
Ethernet connectors	Two RJ-45 connectors on rear of server
10BASE-T cable support	EIA Category 3, 4, or 5 unshielded twisted-pair (UTP) (2 or 4 pair) up to 328 ft (100m)
100BASE-TX cable support	EIA Category 5 UTP (2 pair) up to 328 ft (100m)
Interfaces	
Serial ports	1
Parallel ports	0

USB 2.0	7
Keyboard ports	Use one of the USB ports (PS/2 ports are not provided)
Mouse ports	Use one of the USB ports (PS/2 ports are not provided)
Audio ports	None
VGA ports	1 front and 1 rear
Expansion Options	
8 PCIe non-hot plug slots	1
Power	
Steady-state output power	625W
Autoranging AC mains input	Yes
Power Factor Correction (PFC)	Yes
Maximum hot-swap power supplies	2
Hot-swap power supplies installed	2
Mains input frequency range	47-63 Hz
Operational input voltage ranges	90-137 VAC minimum 180-265 VAC maximum
Environmental	
Air temperature at 0 to 3000 ft (0 to 914m)	50.0 to 95.0°F (10 to 35°C)
Air temperature at 3000 to 7000 ft (914 to 2133m)	50.0 to 90°F (10 to 32°C)
Relative humidity	10 to 80%
BTU rating (maximum configuration)	2840 BTU per hour
Dimensions	
Form factor	Rack-mount 2RU
Rack-mounting	Included for standard third-party rack
Weight-maximum	62 lb (28.1 kg)
Weight-no drives	46.5 lb (21.1 kg)
Height	3.36 in. (8.54 cm)
Width	17.5 in. (44.36 cm)
Depth	27.5 in. (69.8 cm)

The next steps...

ORDER NOW

VIEW ONLINE

Tel: +44 (0)1279 408 777

Email: sales@gocomsys.com

Website: www.gocomsys.com