

Refurbished CISCO EHWIC-4G-LTE-GB Datasheet

CISCO > INTERFACES-MODULES

Cisco High-Speed WAN Interface Cards

Specifications for the Cisco 4G LTE WWAN EHWICs Among Region Theaters

Region Theaters	
Bands	LTE band 1, 3, 7, 8, 20 (800 [band 20], 900 [band 8], 1800 [band 3], 2100 [band 1], 2600 [band 7] MHz)
Theoretical Download/upload speeds	100 Mbps/50 Mbps
Australia	X
United States	X
Canada	X

Antenna Specifications

Antenna 4G-ANTM-OM-CM

Antenna 4G-ANTM-OM-CM	Multiband indoor omnidirectional antenna Ceiling mount
------------------------------	---

Antenna 4G- LTE-ANTM-D

Antenna 4G- LTE-ANTM-D	Cisco 3G and 4G omnidirectional dipole antenna Articulating joint; can be rotated 360 degrees and is capable of maneuvering into three stop positions: 0 degrees, 45 degrees, and 90 degrees Plug-threaded TNC connector: Directly mount the antenna on any Cisco 4G or Cisco 3G wireless ISR EHWIC with a TNC connector; the threads on the connector must comply with the ANSI 7/16-28 UNEF 2B thread specification Multiband swivel-mount dipole antenna Faceplate mount (dual units included with all Cisco 4G WWAN EHWICs)
-------------------------------	---

Antenna extension 4G-AE015-R

Antenna extension 4G-AE015-R	Single-unit antenna extension base (15 ft (457.2 cm))
-------------------------------------	---

Antenna extension 4G-AE010-R

Antenna extension 4G-AE010-R	Single-unit antenna extension base (10 ft [304.8 cm] cable included)
-------------------------------------	--

The next steps...

ORDER NOW

VIEW ONLINE

Tel: +44 (0)1279 408 777

Email: sales@gocomsys.com

Website: www.gocomsys.com