Tel: +44 (0)1279 408 777
Email: sales@gocomsys.com
Website: www.gocomsys.com

# Refurbished CISCO FAN-T2 Datasheet

CISCO > SWITCHES

## Cisco Catalyst 9300 Series Switches

### Stacking accessories

| Model | |
|---|---|
| **STACK-T1-50CM** | Data stack 50 cm (cable option with C9300 SKUs) |
| **STACK-T1-1M** | Data stack 1m (cable option with C9300 SKUs) |
| **STACK-T1-3M** | Data stack 3m (cable option with C9300 SKUs) |
| **C9300L-STACK-KIT** | Stack kit for C9300L SKUs only: Two data stack adapters and one data stack cable |
| **STACK-T3-50CM** | Data stack 50cm cable (default cable with C9300L Stack Kit) |
| **STACK-T3-1M** | Data stack 1m cable (cable option with C9300L Stack Kit) |
| **STACK T3-3M** | Data stack 3m cable (cable option with C9300L Stack Kit) |

### Model Dimensions, Weight, and Mean Time between failures metrics

| Environmental ranges | |
|---|---|
| **Acoustic noise Measured per ISO 7779 and declared per ISO 9296 Bystander positions operating to an ambient temperature of 25°C** | With AC power supply (with 24 PoE+ ports loaded for C9300 SKUs)<br>LpA: 45dB typical, 48 dB max<br>LwA: 5.6B typical, 5.9B max<br>With AC power supply (with half the number of PoE+ ports loaded for C9300L SKUs)<br>LpA: 44dB typical, 47 dB max<br>LwA: 5.5B typical, 5.8B max<br>Typical: Noise emission for a typical configuration<br>Maximum: Statistical maximum to account for variation in production |

### Connectors

| | |
|---|---|
| **Connectors and cabling** | 1000BASE-T ports: RJ-45 connectors, 4-pair Cat 5E UTP cabling<br>Multigigabit-T ports: RJ-45 connectors, 4-pair Cat 5E, Cat 6, Cat 6A UTP cabling<br>1000BASE-T SFP-based ports: RJ-45 connectors, 4-pair Cat 5E UTP cabling<br>SFP transceivers: LC fiber connectors (single-mode or multimode fiber)<br>SFP+ transceivers: LC fiber connectors (single-mode or multimode fiber)<br>QSFP+ transceivers: MPO and LC fiber connectors (single-mode or multimode fiber)<br>QSFP+ connector<br>SFP+ connector<br>Cisco StackWise stacking ports: copper-based Cisco StackWise cabling<br>Cisco StackPower: Cisco proprietary power stacking cables<br>Ethernet management port: RJ-45 connectors, 4-pair Cat 5 UTP cabling<br>Management console port: RJ-45-to-DB9 cable for PC connections |
| **Power connectors** | Customers can provide power to a switch by using the internal power at the back of the switch<br>Internal power supply connector: The internal power supply is an auto-ranging unit. It supports input voltages between 100 (115 for 1100WAC) and 240 VAC. Use the supplied AC power cord to connect the AC power connector to an AC power outlet |

### Power specifications – platinum rated power supplies

| Safety compliance | |
|---|---|
| **LED indicators** | AC OK": Input power to the power supply is OK<br>PS OK": Output power from the power supply is OK |

## Safety and compliance information

| Description | |
|---|---|
| **Description** | Specification |
| **Safety certifications** | UL 60950-1<br>CAN/CSA-C222.2 No. 60950-1<br>EN 60950-1<br>IEC 60950-1<br>AS/NZS 60950.1<br>IEEE 802.3 |
| **Electromagnetic emissions certifications** | 47 CFR Part 15<br>CISPR22 Class A<br>EN 300 386 V1.6.1<br>EN 55022 Class A<br>EN 55032 Class A<br>CISPR 32 Class A<br>EN61000-3-2<br>EN61000-3-3<br>ICES-003 Class A<br>TCVN 7189 Class A<br>V-3 Class A<br>CISPR24<br>EN 300 386<br>EN55024<br>TCVN 7317<br>V-2/2015.04<br>V-3/2015.04<br>CNS13438<br>KN32<br>KN35<br>IEC 61000-6-1<br>EN 61000-6-1<br>Additional Certifications for C9300L SKUs:<br>QCVN 118:2018/BTTTT<br>CISPR24/25<br>CISPR 32 Class A<br>VCCI-CISPR 32 Class A<br>EN55035 |
| **Environmental** | Reduction of Hazardous Substances (ROHS) 5 |

# The next steps...

ORDER NOW

VIEW ONLINE

Tel: +44 (0)1279 408 777

Email: sales@gocomsys.com

Website: www.gocomsys.com