

Refurbished CISCO HDD-7845-H2-72 Datasheet

CISCO > UNIFIED-COMMUNICATIONS

Cisco 7800 Series Media Convergence Servers

Currently Shipping Configuration

Product part number	MCS-7845-H2-CCE2 MCS-7845-H2-CCX2 MCS-7845-H2-IPC2 MCS-7845-H2-RC2 MCS-7845-H2-PSBU
Preload	None
OS included	None
Processor	Dual Intel 5140 2.33-GHz 4M L2
Memory	PC2-5300 667-MHz DDR2 synchronous dynamic RAM (SDRAM) Fully Buffered DIMMs
Hard disks	Four 146-GB SAS 2.5-in. hot-swap
Remote management	HP iLO Advanced License

Previous Shipping Configuration

Product part number	MCS-7845-H2-CCE1 MCS-7845-H2-CCX1 MCS-7845-H2-ECS2 MCS-7845-H2-IPC1 MCS-7845-H2-RC1 MCS-7845-H2-UC1 MCS-7845-H2-S31
Preload	None
OS included	None
Processor	Dual Intel 5140 2.33-GHz 4M L2
Memory	2-GB (two 1-GB) PC2-5300R
Hard disks	Four 72-GB SAS 2.5-in. hot-swap
Remote management	HP iLO Advanced License

Processor Specifications

Maximum processors	2
Processors installed	2
Basic input/output system (BIOS) type	Flash

Memory Specifications

Memory maximum	32 GB
Memory bus clock	667 MHz
Memory technology	PC2-5300 667-MHz DDR2 synchronous dynamic RAM (SDRAM) Fully Buffered DIMMs

Multibit error mitigation	Advanced Error Checking and Correcting (AECC)
Total RAM slots	8

RAID Controller Specifications

Controller model	HP Smart Array P400 Controller
Interface	PCI Express
Cache	256 MB
Battery-backed write cache	Yes
RAID levels supported	1

Hard Disk Specifications

Hot-swappable bays	8
Hard disk interface type	SAS
Hard disk revolutions per minute (rpm)	10,000
Hard disk average seek time	4 ms
Data-transfer rate	300 MB per second

Network Interface Specifications

Ethernet network interface card (NIC)	Dual onboard 10/100/1000
Ethernet connectors	Two RJ-45 connectors on back of server
10BASE-T cable support	EIA Category 3, 4, or 5 unshielded twisted pair (UTP) (2 or 4 pair) up to 328 ft (100m)
100BASE-TX cable support	EIA Category 5 UTP (2 pair) up to 328 ft (100m)
1000BASE-T cable support	EIA Category 6 UTP (recommended), 5E UTP, 5 UTP (2 pair) up to 328 ft (100m)

Interface Port Specifications

Serial ports	1
Parallel ports	0
USB 2.0 ports	5 (2 front, 2 back, and 1 inside)
Keyboard ports	1 PS/2
Mouse ports	1 PS/2
Audio ports	None
System management ports	RJ-45 for HP iLO 2 dedicated Ethernet ports
Video Graphics Array (VGA) ports	1 front and 1 back

Expansion Options and Interfaces

Expansion Options

8x PCIe non-hot plug slots	2
-----------------------------------	---

Replacement Part Numbers

Old Part Number	Replacement Part Number
------------------------	-------------------------

MCS-7845-H2-CCE1	MCS-7845-H2-CCE2
MCS-7845-H2-CCX1	MCS-7845-H2-CCX2
MCS-7845-H2-ECS1	MCS-7845-H2-ECS4
MCS-7845-H2-ECS2	MCS-7845-H2-ECS3
MCS-7845-H2-IPC1	MCS-7845-H2-IPC2
MCS-7845-H2-RC1	MCS-7845-H2-RC2
MCS-7845-H2-UC1	NA

The next steps...

ORDER NOW

VIEW ONLINE

Tel: +44 (0)1279 408 777

Email: sales@gocomsys.com

Website: www.gocomsys.com