

Refurbished CISCO N3K-C3164-ZZ-PE Datasheet

CISCO > SWITCHES

Cisco Nexus 3000 Series Switches

Software Features	
Item	Cisco Nexus 3164Q Switch
Maximum number of longest prefix match (LPM) routes	128,000
Maximum number of IP host entries	120,000
Maximum number of MAC address entries	96,000
Number of multicast routes	16,000, up to 60,000
Number of Interior Gateway Management Protocol (IGMP) snooping groups	8,000, up to 60,000
Number of access control list (ACL) entries	1000 to 4000 egress 4000 to 16000 ingress
Maximum number of VLANs	4000
Maximum number of Virtual Routing and Forwarding (VRF) instances	1000
Maximum number of links in a PortChannel	32
Maximum number of ECMP paths	64
Maximum number of PortChannels	256
Number of active Switched Port Analyzer (SPAN) sessions	4
Maximum number of Rapid per-VLAN Spanning Tree (RPVST) instances	507
Maximum number of Hot Standby Router Protocol (HSRP) groups	490
Maximum number of Multiple Spanning Tree (MST) instances	64
Maximum number of tunnel endpoints (VTEP) and VXLAN physical servers (per VLAN)	10,000

Regulatory Standards Compliance: Safety and EMC	
Specification	
Regulatory compliance	Products should comply with CE Markings per directives 2004/108/EC and 2006/95/EC
Safety	UL 60950-1 Second Edition CAN/CSA-C22.2 No. 60950-1 Second Edition EN 60950-1 Second Edition IEC 60950-1 Second Edition AS/NZS 60950-1 GB4943
EMC: Emissions	47CFR Part 15 (CFR 47) Class A

AS/NZS CISPR22 Class A
CISPR22 Class A
EN55022 Class A
ICES003 Class A
VCCI Class A
EN61000-3-2
EN61000-3-3
KN22 Class A
CNS13438 Class A

EMC: Immunity

EN55024
CISPR24
EN300386
KN24

The next steps...

ORDER NOW

VIEW ONLINE

Tel: +44 (0)1279 408 777

Email: sales@gocomsys.com

Website: www.gocomsys.com