

Refurbished CISCO N9K-C92300YC Datasheet

CISCO > SWITCHES

Cisco Nexus 9000 Series Switches

Cisco Nexus 9200 platform switches	
Model	
Cisco Nexus 92348GC-X	48p 100M/1G Base-T ports + 4p 1/10/25G SPF28,+2p 40/100G QSFP28
Cisco Nexus 92160YC-X Switch	48 x 1/10/25-Gbps SFP+ ports and 6 x QSFP28 ports (4 of the 6 QSFP+ ports are 100Gbps capable ports)
Cisco Nexus 92300YC Switch	48 x 1/10/25-Gbps SFP+ ports and 18 x 40/100-Gbps QSFP28 ports
Cisco Nexus 9272Q Switch	72 x 40-Gbps QSFP+ ports
Cisco Nexus 92304QC Switch	56 x 40-Gbps QSFP+ ports and 8 x 40/100-Gbps QSFP28 ports
Cisco Nexus 9236C Switch	36 x 40/100-Gbps QSFP28 ports

Environmental properties	
Property	
Operating temperature	32 to 104°F (0 to 40°C)
Nonoperating (storage) temperature	-40 to 158°F (-40 to 70°C)
Humidity	5 to 85% (noncondensing)
Altitude	0 to 13,123 ft (0 to 4000m)

Weight	
Component	
Component	Weight
Cisco Nexus 92348GC-X without power supplies or fans	14.12 lb (6.4 kg)
Cisco Nexus 92160YC-X without power supplies or fans	14.12 lb (6.4 kg)
Cisco Nexus 9272Q without power supplies or fans	24.6 lb (11.2 kg)
Cisco Nexus 92304QC without power supplies or fans	25.4 lb (11.5 kg)
Cisco Nexus 9236C without power supplies or fans	18.2 lb (8.3 kg)
Cisco Nexus 92300YC without power supplies or fans	18.6 lb (8.4 kg)
400W AC power supply	2.42 lb (1.1 kg)
400W DC power supply	2.2 lb (1 kg)
500W HV power supply	2.42 lb (1.1 kg)
1200W AC power supply	2.64 lb (1.2 kg)

650W AC power supply	2.42 lb (1.1 kg)
930W DC power supply	2.42 lb (1.1 kg)
1200W HVDC/HVAC power supply	2.42 lb (1.1 kg)
Fan tray: N9K-C9300-FAN3 or N9K-C9300-FAN3-B	1.42 lb (0.64 kg)
Fan tray: NXA-FAN-30CFM-F or NXA-FAN-30CFM-B	0.92 lb (0.4 kg)
Fan tray: NXA-FAN-35CFM-PE or NXA-FAN-35CFM-PI	0.92 lb (0.4 kg)

Regulatory standards compliance: Safety and EMC

Specification

Regulatory compliance	Products should comply with CE Markings according to directives 2004/108/EC and 2006/95/EC
Safety	NEBS UL 60950-1 Second Edition CAN/CSA-C22.2 No. 60950-1 Second Edition EN 60950-1 Second Edition IEC 60950-1 Second Edition AS/NZS 60950-1 GB4943
EMC: Emissions	47CFR Part 15 (CFR 47) Class A AS/NZS CISPR22 Class A CISPR22 Class A EN55022 Class A ICES003 Class A VCCI Class A EN61000-3-2 EN61000-3-3 KN22 Class A CNS13438 Class A
EMC: Immunity	EN55024 CISPR24 EN300386 KN 61000-4 series
RoHS	The product is RoHS-6 compliant with exceptions for leaded-Ball Grid-Array (BGA) balls and lead press-fit connectors

The next steps...

ORDER NOW

VIEW ONLINE

Tel: +44 (0)1279 408 777

Email: sales@gocomsys.com

Website: www.gocomsys.com