

Refurbished CISCO PWR-2504-AC Datasheet

CISCO > WIRELESS

Cisco 2500 Series Wireless Controllers

Cisco 2500 Series Wireless Controller Features and Benefits

| Feature | Benefits |
|--|--|
| Scalability | Supports up to 75 access points Supports up to 1000 clients |
| Ease of Deployment | For quick and easy deployment Access Points can be connected directly to 2504 Wireless LAN Controller via two PoE (Power over Ethernet) ports |
| High Performance | Wired-network speed and nonblocking performance for 802.11n and 802.11ac networks. Supports up to 1 Gbps throughput |
| RF Management | Provides both real-time and historical information about RF interference impacting network performance across controllers, via systemwide Cisco CleanAir technology integration |
| Comprehensive End-to-End Security | Offers CAPWAP-compliant Datagram Transport Layer Security (DTLS) encryption to help ensure full-line-rate encryption between access points and controllers across remote WAN/LAN links |
| End-to-end Voice | Supports Unified Communications for improved collaboration through messaging, presence, and conferencing Supports all Cisco Unified Wireless IP Phones for cost-effective, real-time voice services |
| High-Performance Video | Integrates Cisco VideoStream technology as part of the Cisco medianet framework to optimize the delivery of video applications across the WLAN |
| PCI Integration | Part of Payment Card Industry (PCI) certified architecture, and are well-suited for retail customers who deploy transactional data applications such as scanners and kiosks |
| OfficeExtend | Supports corporate wireless service for mobile and remote workers with secure wired tunnels to the Cisco Aironet 600, 1130, 1140 or 3500 Series Access Points Extends the corporate network to remote locations with minimal setup and maintenance requirements Improves productivity and collaboration at remote site locations Separate service set identifier (SSID) tunnels allow both corporate and personal Internet access Reduced carbon dioxide emissions from a decrease in commuting Higher employee job satisfaction from ability to work at home Improves business resiliency by providing continuous, secure connectivity in the event of disasters, pandemics, or inclement weather |
| Enterprise Wireless Mesh | Allows access points to dynamically establish wireless connections without the need for a physical connection to the wired network Available on select Cisco Aironet access points, Enterprise Wireless Mesh is ideal for warehouses, manufacturing floors, shopping centers, and any other location where extending a wired connection may prove difficult or aesthetically unappealing |
| Environmentally Responsible | Organizations may choose to turn off access point radios to reduce power consumption during off-peak hours |
| Mobility, Security and Management for IPv6 & Dual-Stack Clients | Secure, reliable wireless connectivity and consistent end-user experience Increased network availability by proactive blocking of known threats Equips administrators for IPv6 troubleshooting, planning, client traceability from a common wired and wireless management system |
| Guest Anchor and Wired Guest Access | Supports up to 15 guest anchor Ethernet over IP (EoIP) tunnels for path isolation of guest traffic from enterprise data traffic Extends the guest access services to the wired clients on par with other WLAN Controllers |

Product Specifications for the Cisco 2500 Wireless Controller

| Item | |
|------|---------------|
| Item | Specification |

| | |
|--|--|
| Wireless Standards | IEEE 802.11a, 802.11ac, 802.11b, 802.11g, 802.11d, WMM/802.11e, 802.11h, 802.11k, 802.11n, 802.11r, 802.11u, 802.11w, 802.11ac |
| Wired/Switching/Routing | IEEE 802.3 10BASE-T, IEEE 802.3u 100BASE-TX specification, 1000BASE-T, and IEEE 802.1Q VLAN tagging |
| Data Request for Comments (RFCs) | RFC 768 UDP RFC 791 IP RFC 2460 IPv6 (passthrough bridging mode only) RFC 792 ICMP RFC 793 TCP RFC 826 ARP RFC 1122 Requirements for Internet Hosts RFC 1519 CIDR RFC 1542 BOOTP RFC 2131 DHCP RFC 5415 CAPWAP Protocol Specification |
| Security Standards | Wi-Fi Protected Access (WPA) IEEE 802.11i (WPA2, RSN) RFC 1321 MD5 Message-Digest Algorithm RFC 1851 The ESP Triple DES Transform RFC 2104 HMAC: Keyed Hashing for Message Authentication RFC 2246 TLS Protocol Version 1.0 RFC 2401 Security Architecture for the Internet Protocol RFC 2403 HMAC-MD5-96 within ESP and AH RFC 2404 HMAC-SHA-1-96 within ESP and AH RFC 2405 ESP DES-CBC Cipher Algorithm with Explicit IV RFC 2406 IP Encapsulating Security Payload (ESP) RFC 2407 Interpretation for ISAKMP RFC 2408 ISAKMP RFC 2409 IKE RFC 2451 ESP CBC-Mode Cipher Algorithms RFC 3280 Internet X.509 PKI Certificate and CRL Profile RFC 3602 The AES-CBC Cipher Algorithm and Its Use with IPsec RFC 3686 Using AES Counter Mode with IPsec ESP RFC 4347 Datagram Transport Layer Security RFC 4346 TLS Protocol Version 1.1 |
| Encryption | WEP and Temporal Key Integrity Protocol-Message Integrity Check (TKIP-MIC): RC4 40, 104 and 128 bits (both static and shared keys) Advanced Encryption Standard (AES): CBC, CCM, Counter Mode with Cipher Block Chaining Message Authentication Code Protocol (CCMP) DES: DES-CBC, 3DES Secure Sockets Layer (SSL) and Transport Layer Security (TLS): RC4 128-bit and RSA 1024- and 2048-bit DTLS: AES-CBC |
| Authentication, Authorization, and Accounting (AAA) | IEEE 802.1X RFC 2548 Microsoft Vendor-Specific RADIUS Attributes RFC 2716 PPP EAP-TLS RFC 2865 RADIUS Authentication RFC 2866 RADIUS Accounting RFC 2867 RADIUS Tunnel Accounting RFC 3576 Dynamic Authorization Extensions to RADIUS RFC 3579 RADIUS Support for EAP RFC 3580 IEEE 802.1X RADIUS Guidelines RFC 3748 Extensible Authentication Protocol Web-based authentication TACACS support for management users |
| Management | SNMP v1, v2c, v3 RFC 854 Telnet RFC 1155 Management Information for TCP/IP-Based Internets RFC 1156 MIB RFC 1157 SNMP RFC 1213 SNMP MIB II RFC 1350 TFTP RFC 1643 Ethernet MIB RFC 2030 SNMP RFC 2616 HTTP RFC 2665 Ethernet-Like Interface types MIB RFC 2674 Definitions of Managed Objects for Bridges with Traffic Classes, Multicast Filtering, and Virtual Extensions RFC 2819 RMON MIB RFC 2863 Interfaces Group MIB RFC 3164 Syslog RFC 3414 User-Based Security Model (USM) for SNMPv3 RFC 3418 MIB for SNMP RFC 3636 Definitions of Managed Objects for IEEE 802.3 MAUs Cisco private MIBs |
| Management Interfaces | Designed for use with Cisco Wireless Control System |

| | |
|-----------------------------------|---|
| | Web-based: HTTP/HTTPS individual device manager Command-line interface: Telnet, SSH, serial port |
| Interfaces and Indicators | Console port: RJ-45 connector Network: Four 1 Gbps Ethernet (RJ-45) LED indicators: Link Activity (each 1 Gigabit Ethernet port), Power, Status, Alarm |
| Physical and Environmental | Dimensions: 1.73 x 8.00 x 6.75 in. (43.9 x 203.2 x 271.5mm) Weight: 3.5 lbs (with power supply) Temperature: Operating: 32 to 104 °F (0 to 40°C) Storage: -13 to 158°F (-25 to 70°C) Humidity: Operating humidity: 10 to 95 percent, noncondensing Storage humidity: Up to 95 percent Power adapter: Input power: 100 to 240 VAC; 50/60 Hz Heat dissipation: 72 BTU/hour |
| Regulatory Compliance | Safety: UL 60950-1, 2 Edition EN 60950:2005 EMI and susceptibility (Class B): U.S.: FCC Part 15.107 and 15.109 Canada: ICES-003 Japan: VCCI Europe: EN 55022, EN 55024 |

The next steps...

ORDER NOW

VIEW ONLINE

Tel: +44 (0)1279 408 777

Email: sales@gocomsys.com

Website: www.gocomsys.com