

Refurbished CISCO UCSB-B200-M5 Datasheet

CISCO > SERVERS-UNIFIED-COMPUTING

Cisco UCS B-Series Blade Servers

Specifications	
Item	
Item	Specifications
Processors	Up to 2 Intel Xeon Scalable processors (1 or 2)
Memory	24 DDR4 DIMM slots: 16, 32, 64, and 128 GB at up to 2933 MHz
Intel Optane DC Persistent Memory	12 DIMM slots: 128, 256, and 512 GB at up to 2666 MHz
mLOM	mLOM slot for Cisco UCS VIC 1440 or 1340
Mezzanine adapter (rear)	1 rear mezzanine adapter for: Cisco UCS VIC 1480 or 1380 mezzanine card Cisco port expander mezzanine card Cisco nVIDIA P6 GPU rear mezzanine card Cisco blade NVMe storage card
Mezzanine adapter (front)	1 front mezzanine adapter for: Cisco FlexStorage 12-Gbps SAS RAID Controller Cisco FlexStorage 12-Gbps SAS RAID Controller with 2-GB cache Cisco FlexStorage NVMe or pass-through module Cisco nVIDIA P6 GPU front mezzanine card
Internal storage	2 hot-pluggable front-access 2.5-inch drives: HDD: 10,000 or 15,000 RPM with up to 1.8 TB per drive SSD: Enterprise Performance and Value SSDs with up to 7.6 TB per drive NVMe: Up to 7.7 TB per drive Note: Drives require a RAID or pass-through controller in the front mezzanine adapter slot. Choice of either: 2 internal SD cards (32-, 64-, or 128-GB with boot-mirroring or Up to 2 M.2 SATA drives (240 or 960 GB) supported via LSI software RAID
Management	Cisco Intersight software Cisco UCS Manager Release 4.0(4) Cisco UCS Central Software Cisco UCS Director Cisco UCS Performance Manager
Temperature: operating	50° to 95°F (10° to 35°C)
Temperature: nonoperating:	-40° to 149°F (-40° to 65°C)
Humidity: operating	5% to 93% noncondensing
Humidity: nonoperating	5% to 93% noncondensing
Altitude: operating	0 to 10,000 ft (0 to 3000m); maximum ambient temperature decreases by 1°C per 300m
Altitude: nonoperating	40,000 ft (12,000m)

System requirements	
Item	Requirements
Blade chassis	Cisco UCS 5108 Blade Server Chassis
Fabric interconnect	Cisco UCS 6248 UP, 6296UP, 6332- 16UP, 6332, 6324, and 6454 Fabric Interconnects
Fabric extender	Cisco UCS 2204, 2208, 2304 Fabric Extenders
Cisco UCS Manager software	Current: Release 4.0(4) or later; refer to the UCSM Release Notes for supported releases for this

platform.

The next steps...

ORDER NOW

VIEW ONLINE

Tel: +44 (0)1279 408 777

Email: sales@gocomsys.com

Website: www.gocomsys.com