

Refurbished CISCO WS-C2960X-48FPD-L Datasheet

CISCO > SWITCHES

Cisco Catalyst 2960-X Series Switches

Cisco Catalyst 2960-X and 2960-XR Series hardware

Hardware specifications

Flash memory	128 MB for LAN Base and IP Lite SKUs, 64 MB for LAN Lite SKUs
DRAM	512 MB for LAN Base and 256 MB for LAN Lite
CPU	APM86392 600 MHz dual core
Console ports	USB (Type B), Ethernet (RJ-45)
Storage interface	USB (Type A) for external flash storage
Network management interface	10/100 Mbps Ethernet (RJ-45)

Cisco Catalyst 2960-X and 2960-XR Series forwarding performance

2960-X models

Cisco Catalyst 2960X-48FPD-L	130.9 Mpps
Cisco Catalyst 2960X-48LPD-L	130.9 Mpps
Cisco Catalyst 2960X-24PD-L	95.2 Mpps
Cisco Catalyst 2960X-48TD-L	130.9 Mpps
Cisco Catalyst 2960X-24TD-L	95.2 Mpps
Cisco Catalyst 2960X-48FPS-L	107.1 Mpps
Cisco Catalyst 2960X-48LPS-L	107.1 Mpps
Cisco Catalyst 2960X-24PS-L	71.4 Mpps
Cisco Catalyst 2960X-24PSQ-L	71.4 Mpps
Cisco Catalyst 2960X-48TS-L	107.1 Mpps
Cisco Catalyst 2960X-24TS-L	71.4 Mpps
Cisco Catalyst 2960X-48TS-LL	104.2 Mpps

2960-XR models

Cisco Catalyst 2960XR-48FPD-I	130.9 Mpps
Cisco Catalyst 2960XR-48LPD-I	130.9 Mpps
Cisco Catalyst 2960XR-24PD-I	95.2 Mpps
Cisco Catalyst 2960XR-48TD-I	130.9 Mpps
Cisco Catalyst 2960XR-24TD-I	95.2 Mpps
Cisco Catalyst 2960XR-48FPS-I	107.1 Mpps
Cisco Catalyst 2960XR-48LPS-I	107.1 Mpps
Cisco Catalyst 2960XR-24PS-I	71.4 Mpps
Cisco Catalyst 2960XR-48TS-I	107.1 Mpps

Cisco Catalyst 2960-X Series mechanical specifications

Model	
Centimeters (H x D x W)	1.75 x 14.5 x 17.5
Pounds	4.5 x 36.8 x 44.5
Kilograms	12.9
Model	5.8

Safety and compliance

Specification	
Safety	UL 60950-1 Second Edition CAN/CSA-C22.2 No. 60950-1 Second Edition EN 60950-1 Second Edition IEC 60950-1 Second Edition AS/NZS 60950-1
EMC – emissions	47CFR Part 15 (CFR 47) Class A AS/NZS CISPR22 Class A CISPR22 Class A EN55022 Class A ICES003 Class A VCCI Class A EN61000-3-2 EN61000-3-3 KN22 Class A CNS13438 Class A
EMC – immunity	EN55024 CISPR24 EN300386 KN24
Environmental	Reduction of Hazardous Substances (RoHS) including Directive 2011/65/EU
Telco	Common Language Equipment Identifier (CLEI) code
US government certifications	USGv6 and IPv6 Ready Logo

Features supported in Cisco DNA Essentials for Cisco Catalyst 2960-X and Cisco Catalyst 2960-XR Series

Category	
Category	Features
Network visibility	DNS-AS, Full Flexible NetFlow
Day-zero network bring-up automation	Cisco Network Plug-and-Play application
Cisco DNA Center	Discovery, inventory, topology, software image management
Network monitoring	Device 360

The next steps...

ORDER NOW

Tel: +44 (0)1279 408 777

Email: sales@gocomsys.com

VIEW ONLINE

Website: www.gocomsys.com